

Blue Ridge Wire & Cable

1310 McWatters Road #705

Ottawa, Ontario K2C 3N8

Phone: 613-820-1587

Cell: 613-617-9641

gary@blueridgewire.ca

Line Card

September 15, 2017

COMPONENT WIRE

TEW – CL1053 – CL1251 – CL1503 - CL1254 –
CL1503 – GTF – SIS

Retractable Cords

VFD (Variable Frequency Drive) Cable

Low Smoke Zero Halogen Tray Cable

- » LSZH Teck90 Cable

Medium Voltage Shielded Power Cable / UD /
URD Concentric Neutral Cable

- » Copper or Aluminum
- » 5KV through 46KV

Aerial Jumper Cable

- » 15KV – 25KV – 35KV

Utility Grade Grounding Cable

- » 600V
- » Clear PVC Jacket
- » Yellow or Orange Thermoplastic Rubber Jacket per ASTM F855 Type 1 specs.

MINING CABLES

Type W Portable Power Cable

- » 90C 2000V
- » Single Conductor through 5 Conductors
- » 8 AWG through 500MCM

Type G & G-GC Cable

- » 90C 2000V
- » 3 & 4 Conductor
- » 8 AWG through 500MCM

Type SHD-GC Cable CSA certified & EMR & MSHA approved

- » 2KV – 5KV – 8KV – 15KV – 25KV

DLO 2000V Diesel Electric Locomotive Cable

- » 90C CSA FT4 sizes 1/0 & large
- » 8 AWG through 1111MCM

Mine Power Feeder Cable MP-GC

- » 5000/15000V

Arc Welding Cable

- » 6 AWG – 500MCM
- » CSA & Non CSA

Stacker/Reclaimer Cable

Control & Power Tray Cables

- » XLPE/PVC 600V & 1000V FT4

Pendflex

Pendant & Reeling Cable

Flat Festoon Cable

- » PVC or Neoprene Jacket

Type SJOOW & SOOW

- » Black - Yellow

Type SEOOW CSA STOOW (TPE)

- » 600V 105C (-50C)
- » Black – White - Yellow

PV Photovoltaic Wire

Armoured Cables similar to Teck90

- » 200 Deg. C insulation & Jacket

HDPE Geophysics Wire

- » 14 AWG / 12 AWG / 10 AWG
- » Red – Orange – Yellow

HIGH TEMPERATURE WIRE

Tefzel

- » Mil-W-22759/16
- » 600V 150C
- » 18 AWG through 8 AWG

Teflon

- » Type E 600V 200C
- » Type EE 1000V 200C
- » Type K 600V 200C
- » Type KK 1000V 200C

Type SEW-2

- » 600V 200C
- » 600V 150C –
- » CL2001 (SEW-2)
- » CL1501 (SEWF-2)

TGGT

- » 600V 250C

MG

- » 600V 450C commercially rated @ 538C (1000F)

FG2000

- » 600V 450C CSA
- » UL - for use in extreme heat conditions
- » Withstands temperatures as high as 3000F to allow for controlled shutdown

Integraflame CIC

- » Strength Under Fire – where exposure to flame is a risk
- » Contact our Sales Office for details on Compliance information.

Stacker/Reclaimer Cable

Control & Power Tray Cables

XLPE/PVC

- » 600V & 1000V FT4 (CSA)

Pendflex

Pendant & Reeling Cable Yellow Jacket

Flat Festoon Cable

- » PVC or Neoprene Jacket

Type SJOOW & SOOW

- » Black - Yellow

Type SEOOW CSA STOOW (TPE)

- » 600V 105C (-50C)
- » Black – White - Yellow

PV Photovoltaic Wire

Cableclad -2 Armoured Cables

- » similar to Teck90 except rated 200 Deg. C insulation & Jacket.

Exane - XLPO Locomotive Cable

- » LXE DAA1069A- DAA1093A
- » 600V + 2000V 125 Deg.C

Exane – XLPO – Rapid Transit Cable

- » TXE DAA1068A
- » 110C 600V + 2000V

OVERHEAD UTILITY WIRES & CABLES

AAC-ASC-ACSR-AAAC

- » Aluminum Alloy 6201-ACAR

Oil Rig Cable

- » Type P Mud Resistant –Zero Halogen
- » Bare or Tinned Copper
- » Solid or Stranded or Extra-Flexible
- » Soft Drawn – Medium Hard Drawn (MHD) – Hard Drawn (HD)

Trolley Wire

- » Round-Grooved – Fig.8 , Fig-9 Deep Section
- » Flat- Oval-Round-Tubular-Bare or Tinned Copper Braid